


CABLES

**PHASE STABLE OVER TEMPERATURE
FLEXIBLE MICROWAVE COAXIAL CABLE**



REF : HY360PS

SPECIFICATIONS MECANIKES / MECHANICAL SPECIFICATIONS

Type de câble / Cable type	
Températures d'utilisation / Temperature range	-55 °C ~ +125 °C
Rayon de courbure minimum / Minimum bend radius	18 mm (stat) / 36 mm (dyn)
Poids / Weight	33 kg/km

SPECIFICATIONS ELECTRIQUES / ELECTRICAL SPECIFICATIONS

Frequence d'utilisation / Frequency range	DC ~ 40 GHz
Impédance / Impedance	50 Ohms
Capacité / Capacitance	80 pF/m
Vitesse de propagation / Velocity of propagation	82 %
Efficacité de blindage / Shielding effectiveness	100 dB (min)
Retard linéique / Time delay	4.02 ns/m
Tension d'utilisation / Voltage Withstand	2000 V


CONSTRUCTION ET MATERIAUX / CONSTRUCTION AND MATERIAL SPECIFICATIONS

Conducteur central / Inner conductor	Solid SPC wire Ø 0,93 mm
Diélectrique / Dielectric	Proprietary Ø 2,55 mm
Tresse de blindage / Inner shield braid	Flat SPC Ø 2,72 mm
Feuillard inter-blindage / Interlayer	Al foil Ø 2,85 mm
Seconde tresse de blindage / Outer shield braid	SPC wire Ø 3,15 mm
Gaine / Jacket	FEP Ø 3,60 mm

ATTENUATION ET PUISSANCE / ATTENUATION AND POWER HANDLING

Frequency (MHz)	500	1000	3000	6000	8000	9000	10000	12000	18000	26500	40000
Typical attenuation (dB/m)	0,349	0,500	0,892	1,299	1,522	1,626	1,724	1,911	2,410	3,022	3,869
Typical attenuation (dB/m) = (1,5143376 x √(FMHz)) + (0,0021 x FMHz) ÷ 100 with VSWR = 1.0 and Temperature = 25 °C											
Max power handling (W/cw)	711	505	278	191	163	153	144	130	103	82	64

ATTENUATION (dB/m) / TYPICAL ATTENUATION (dB/m) vs FREQUENCY (MHz)



HYTEM - ISO9001 CERTIFIED

2 Bis Rue du Bois Fourgon - 91580 VILLECONIN

T : +33(0) 1 60 80 59 00 - F : +33 (0) 1 60 80 33 22 - hytem@hytem.net - www.hytem.net

Ref : HY360PS

Ed : 01/07/2024

Page : 1/2

Specific parameters

Phase Change VS Bending (°/GHz)

±0.3

Phase Change VS Temperature

≤350 PPM @ -55 / +85°C

